



-65°C ULTRA LOW TEMPERATURE CHEST FREEZER BKD-502

-60°C ULTRA LOW TEMPERATURE FREEZER BKD-502

-65°C ULTRA LOW TEMPERATURE CHEST FREEZER



SPECIFICATIONS

Model	BKD-502
Capacity	200 L
Temperature Range	-25°C ~ -65°C
Climate class	N
Unit dimensions	1390*860*930 mm
Interior dimensions	710*510*580 mm
Power supply	220V/50Hz or 115V/60Hz
Rated input	350 W
Power consumption	4.20 kW.h/24h (FRO)
Refrigerants	Mixed CFC free
Compressor	World brand compressor
Thermostat	Brand Electronic controller
Temperature display	Digital display
Evaporator	Wall type copper tube
Condenser	Wall type copper tube
Fan for condenser	German brand, EBM
Insulation thickness	125 mm
Material of interior	SUS 304 stainless steel
Door	Foamed door, top open
Door handle	Recessed handle with lock
Baskets	N/A
Wheels	4 pieces, Foot Master Casters
Net weight	125 kg
Alt Name	-65°C Ultra Low Temperature Chest Freezer

APPLICATIONS

The -65°C ultra low temperature chest freezers are used for freezing storage of biological samples and products in the fields of universities, institutes, bio-pharmacy, cancer research, vaccine storage and space exploration, many other specialized industries; the freezer also can be used for fresh storage of deep seafood such as tuna, at super low temperature in Japanese restaurants, hotels, high clubs and seafood markets.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com