



-86°C ULTRA LOW TEMPERATURE CHEST FREEZER BKD-711

-86°C ULTRA LOW TEMPERATURE FREEZER BKD-711

-86°C ULTRA LOW TEMPERATURE CHEST FREEZER



SPECIFICATIONS

Model	BKD-711
Capacity	300 L
Temperature Range	-40°C ~ -86°C
Climate class	N
Unit dimensions	1690*860*930 mm
Interior dimensions	1010*510*580 mm
Power supply	220 V/50Hz or 115V/60Hz
Rated input	550 W
Power consumption	7.00 kW.h/24h (FRO)
Refrigerants	Mixed CFC free
Compressor	SECOP or Embraco
Thermostat	Brand Electronic controller
Temperature display	Digital display
Alarms	Over temp, sensor fault alarms
Evaporator	Wall type copper tube
Condenser	Al finned copper tube
Fan for condensing	German brand, EBM
Insulation thickness	125 mm
Material of interior	SUS 304 stainless steel
Door	Foamed door, top open
Door handle	Aluminum door handle
Wheels	4 pieces, Foot Master casters
Net weight	150 kg
Alt Name	-86°C Ultra Low Temperature Chest

APPLICATIONS

The -86°C ULT upright freezers are used in fields of biological research, clinics and health and epidemic prevention, industries, fresh keeping of foods etc., for freezing storage of biological samples and biologics, bio-chemical re-agents; for low temperature testing and treatment of electronic and metal materials parts; also used for fresh keeping storage of sashimi of deep sea foods and high grade foods at ultra low temperature.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com