



-86°C ULTRA LOW TEMPERATURE UPRIGHT FREEZER BKD-803

-86°C ULTRA LOW TEMPERATURE FREEZER BKD-803

-86°C ULTRA LOW TEMPERATURE UPRIGHT FREEZER



SPECIFICATIONS

Model	BKD-803
Capacity	80L
Temperature Range	-40°C ~ -86°C
Climate class	N
Unit dimensions	700*690*1275 mm
Interior dimensions	380*410*500 mm
Power supply	220V/50Hz or 115V/60Hz
Rated input	450 W
Power consumption	5.30 kW.h/24h (FRO)
Refrigerants	Mixed CFC free
Compressor	World brand compressor
Thermostat	Brand Electronic controller
Temperature display	Digital display
Alarms	Over temp. , sensor fault alarms
Evaporator	Wall type copper tube
Condenser	Al finned copper tube
Fan for condenser	German brand, EBM
Insulation thickness	120 mm
Material of interior	SUS 304 stainless steel
Shelves	One piece, stainless steel
Door	Foamed door, Swing
Door handle	OX-Head handle with lock
Inner doors	2 pieces, stainless steel
Wheels	4 pieces, Footmaster casters
Net weight	80 kg
Alt Name	-86°C Ultra Low Temperature Upright Freezer

APPLICATIONS

The -86°C ULT upright freezers are used in fields of biological research, clinics and health and epidemic prevention, industries, fresh keeping of foods etc., for freezing storage of biological samples and biologics, bio-chemical re-agents; for low temperature testing and

treatment of electronic and metal materials parts; also used for fresh keeping storage of sashimi of deep sea foods and high grade foods at ultra low temperature.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com