



-86°C ULTRA LOW TEMPERATURE UPRIGHT FREEZER BKD-812

-86°C ULTRA LOW TEMPERATURE FREEZER BKD-812

-86°C ULTRA LOW TEMPERATURE UPRIGHT FREEZER



SPECIFICATIONS

Model	BKD-812
Capacity	938 L
Temperature Range	-40°C ~ -86°C
Climate class	N
Unit dimensions	1320*995*1975 mm
Interior dimensions	1000*700*1300 mm
Power supply	220 V/50Hz or 230V/60Hz
Rated input	1300 W
Power consumption	16.50 kW.h/24h (FRO)
Refrigerants	Mixed CFC free
Compressor	Two sets, World brand compressor
Thermostat	Brand Electronic controller
Temperature display	Digital display
Alarms	Over temp. , sensor fault alarms
Evaporator	Wall type copper tube
Condenser	Al finned copper tube
Fan for condenser	German brand, EBM
Insulation thickness	130 mm
Material of interior	SUS 304 stainless steel
Shelves	3 pieces, stainless steel
Door	Foamed door, Swing
Door handle	Eagle-mouth shape with lock
Inner doors	4 pieces, stainless steel
Wheels	4 pieces, Footmaster casters
Net weight	320 kg
Alt Name	-86°C Ultra Low Temperature Upright Freezer

APPLICATIONS

The -86°C ULT upright freezers are used in fields of biological research, clinics and health and epidemic prevention, industries, fresh keeping of foods etc., for freezing storage of biological samples and biologics, bio-chemical re-agents; for low temperature testing and

treatment of electronic and metal materials parts; also used for fresh keeping storage of sashimi of deep sea foods and high grade foods at ultra low temperature.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com