



FLOOR STANDING LOW SPEED CENTRIFUGE BKE-2201

LOW SPEED CENTRIFUGE BKE-2201

FLOOR LARGE CAPACITY LOW SPEED CENTRIFUGE



Intelligent control system

7inches HD Large LCD touch screen display

The acceleration and deceleration mode can be set, and the speed RCF setting mode is provided. Users can arbitrarily set the speed up and down time and automatically calculate the RCF value.

5 directly program groups shortcut key, and store more than 99 program groups

10 gears acceleration /deceleration with linear drive.

User management function setting the password to lock the machine

Excellent kernel performance

Microcomputer control ,AC frequency conversion brush-less motor with fast speed and stable operation.

Two modes can be set: start timing/arrival revolution timing.

SPECIFICATIONS

Model	BKE-2201
Max. Speed	6500rpm
Max. RCF	6680xg
Max. Capacity	6x1000ml
Timer	1s~99h59min59s
Revolutions/min	±10r/min
Voltage	AC 220±22V 50Hz 15A
Power	1500W
Noise Level	≤ 65dB(A)
Size	905x755x1070 (mm)
Net Weight	265kg
Rotor automatic recognition	Yes
Alt Name	Floor Large Capacity Low Speed Centrifuge

ACCESSORIES FOR PURCHASE

No	Name	Capacity	Max Speed(r/min)	Max RCF(xg)
1	Angle rotor	6x250ml	6500rpm	6610xg
2		6x300ml	6500rpm	6610xg
3		6x500ml	6000rpm	6680xg
4	Swing-out rotor	6x1000ml(Round bucket)	4200rpm	5100xg
5		6x1000ml(Square bucket)	4200rpm	5100xg
6		Automatic uncap 168x2~7ml (blood collection tube)	4200rpm	5100xg

FEATURES

Intelligent control system

7inches HD Large LCD touch screen display

The acceleration and deceleration mode can be set, and the speed RCF setting mode is provided. Users can arbitrarily set the speed up and down time and automatically calculate the RCF value.

5 directly program groups shortcut key, and store more than 99 program groups

10 gears acceleration /deceleration with linear drive.

User management function setting the password to lock the machine

Excellent kernel performance

Microcomputer control ,AC frequency conversion brush-less motor with fast speed and stable operation.

Two modes can be set: start timing/arrival revolution timing.

Special thermal insulation inside the machine ensure it running temperature more stable.

Energy-efficient Eco friendly CFC free refrigerating system,temperature between -20°C~+40°C.

Careful and safe

Bloodbank station specialized 6*1000ml square bucket with bloodbag adapters

With rotor automatic identification system .

Over speed,over heat,unbalance protections with auto lid lock.

Steel Structure,centrifuge chamber made of stainless steel with Environmentally friendly anti-corrosion coating treatment.

Electronic self suck door and electromagnetic induction door protection identification.

Intimate detail design

Ergonomic, low opening height, close the centrifuge cover with one press.

Special noise reduction system.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com