



DUCTED FUME HOOD BKF-1002

DUCTED FUME HOOD BKF-1002

ALL STEEL FUME HOOD FX-FH SERIES



Water, electricity, gas, ventilation one system, equipped with multi-functional power sockets, easy to use other electrical equipment in the laboratory process. The use of quick opening valve is convenient for water use during the experiment. The front baffle is a glass door that can be moved up and down, and the top is a low-speed exhaust fan, which can smoothly discharge harmful gases during the experiment. The bottom of the working face is equipped with a stainless steel sink, which can remove the disinfectant and laboratory residue from a row of sinks by washing, and keep the experimental environment safe and reliable.

SPECIFICATIONS

Model	BKF-1002
Internal Dimensions (W*D*H)	988*655*1200
External Dimensions (W*D*H)	1200*850*2350
wind speed	0.25~0.45m/s range adjustable
Intake pressure	>0.5Pa
Power supply	AC single phase 220V/50HZ
Maximum power	400W
Weight	130KG
UV lamp specification and quantity	28Wx1
Alt Name	All Steel Fume Hood FX-FH Series

APPLICATIONS

The fume hood is a common laboratory equipment used in the laboratory, which needs to discharge harmful gases, and needs cleaning and blow down during the experiment.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com