



ILLUMINATION INCUBATOR BKF-10202

ILLUMINATION INCUBATOR BKF-10202

ILLUMINATION INCUBATOR



1. The working chamber adopts high-quality stainless steel.
2. Intelligent programmable control system, dual sided illumination with high light source.
3. Compressor is fluorine free and environmentally friendly for refrigeration, with forced circulation by fans.
4. The front door is sealed with magnetic tape for excellent performance and easy opening.
5. Equipped with multiple safety measures such as compressor overheat protection, instrument fault protection, etc. to ensure experimental safety.

SPECIFICATIONS

Model	BKF-10202
Capacity	150L
Temperature range	10-50 °C when illuminated 0-50 °C when not illuminated
Internal size (W*D*H)	400*500*750mm
External size (W*D*H)	640*640*1360mm
Constant temperature method	Forced convection, heating and cooling balance
Temperature resolution	0.1°C
Temperature fluctuation	0.5°C
Temperature accuracy	±1°C (at 37°C)
Light source illuminance	0-12000LX (LED light source)
Internal material	Stainless steel
External material	cold rolled steel plate is coated with antibiotic resistant coating
Heater	Stainless steel heater
Display	LCD display
Voltage	AC 220V 50HZ
Power consumption	0.6KW
Alt Name	Illumination Incubator

APPLICATIONS

It can be used for light culture of microorganisms, cell tissues, seedlings, insects, and small animals.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com