



VERTICAL LAMINAR AIRFLOW BKF-204

VERTICAL LAMINAR AIRFLOW BKF-204

SW-CJ SERIES VERTICAL AIR SUPPLY LAMINAR FLOW CABINET



SPECIFICATIONS

Model	BKF-204
Internal Dimensions (W*D*H)	880*650*580
External Dimensions (W*D*H)	1040*720*1600
Cleanliness level	Level 100 @ $\geq 0.5 \mu\text{M}$ (Federal 209E)
Colony count	≤ 0.5 pieces/dish · hour (Φ 90mm culture plate)
Average wind speed	0.25~0.45m/s
Noise	$\leq 62\text{dB(A)}$
Vibration half peak	$\leq 0.5\mu\text{M}$
Illuminance	$\geq 300\text{Lx}$
Power supply	AC single phase 220V/50Hz
Maximum power	490W
Weight	90kg
Applicable number of people	Single person/Double side
Specification and quantity of high-efficiency filters	865x555x50
Specification and quantity of fluorescent/ultraviolet lamps	12Wx/20W
Alt Name	vertical air supply laminar flow cabinet

APPLICATIONS

Adopting an arbitrary positioning sliding door system.

The outer shell is welded with cold rolled sheet, and the surface is electrostatically sprayed with plastic.

The workbench is made of SUS304 brushed stainless steel, which is corrosion-resistant and easy to clean.

Safety interlock between lighting and sterilization systems, with UV lamp timing function.

Digital LCD control interface, more user-friendly design.

Vertical quasi closed countertop, the formation of a downward flow air curtain in the operating room, can effectively prevent external gas input and clean the operating area.

Equipped with HEPA high-efficiency air filter and primary filter for initial filtration, it can effectively extend the service life of the high-efficiency filter.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com