



HORIZONTAL LAMINAR AIRFLOW BKF-401

HORIZONTAL LAMINAR AIRFLOW BKF-401

SW-CJ-1FB SW-CJ-2FB LAMINAR FLOW CABINET



SPECIFICATIONS

Model	BKF-401
Internal Dimensions (W*D*H)	870*520*620
External Dimensions (W*D*H)	1030*740*1800
Cleanliness level	Grade 100 @ $\geq 0.5\mu\text{M}$ (Federal 209E)
Colony count	≤ 0.5 PCS/dish · hour ($\Phi 90\text{mm}$ culture plate)
Average wind speed	0.25~0.45m/s
Noise	$\leq 62\text{dB(A)}$
Vibration half peak	$\leq 5\mu\text{M}$ (x, y, z direction)
Illuminance	$\geq 300\text{Lx}$
Power supply	AC Single-phase 220V/50Hz
Maximum power	500W
Weight	90kg
Applicable number of people	Single person/Single side
Specification and quantity of high-efficiency filters	855x450x50x/820x565x50
Specification and quantity of fluorescent/ultraviolet lamps	20Wx/20W
Alt Name	Laminar flow cabinet

APPLICATIONS

Humanized design fully takes into account the actual needs of users, according to the counterweight balance structure can make the operating window of the glass sliding door to achieve arbitrary positioning, making the experiment more convenient and simple.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com