



SEAL TESTER BKF-4401

SEAL TESTER BKF-4401

MFY-02 SEALING TESTER



The host adopts dual mode design to support compressed air and vacuum pump for user choice.

English posts are supported. You can change the language as required.

Microcomputer control, pumping pressure, pressure holding, pressure replenishing, timing, backblowing full automatic operation.

The device is equipped with an LCD screen to support data preset and power off memory to ensure the accuracy of test data.

Using the world famous SMC imported pneumatic components, durable, stable and reliable performance.

SPECIFICATIONS

Model	BKF-4401
Vacuum	-90kPa
Accuracy	Level 0.5 (Better than Level 1)
Effective dimensions of vacuum chamber	Φ270 mm x 210 mm (H) (standard) \nΦ270 mm x 400mm (H) (standard) \nΦ270mm x 585 mm (H) (purchased separately) \nΦ370mm x 330mm (H) (highly customizable)
Air pressure	0.7MPa
Air connection	Φ6mm polyurethane pipe
Overall dimension (L)x(B)x(H)	300mmx380mmx450mm
Power supply	AC 220V 50Hz
Net weight	20KG
Alt Name	Sealing tester



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com