PRODUCT CATALOG

# FRP FUME HOOD BKJ-802

ISO9001 CERTIFIED

www.biolabscientific.com

# FRP FUME HOOD BKJ-802

FRP FUME HOOD

1. Corrosion resistance: FRP has a wide range of corrosion resistance, it is suitable for
acid gas, toxic and harmful gases and organic solvent gas and dust production operation
post and occasions.
2. Operation table: 12.7mm thick phenolic resin board, acid and alkali resistance, moisture proof, anti shock.
3. Adjust door: two section type safety tempered glass, stepless balanced lifting, pulling
up and down to stay in any position.
4. Lighting: fluorescent lamp light source and anti-corrosion, isolation light a

## SPECIFICATIONS

| Model | BKJ-802 |
|---|---|
| Internal Size (W*D*H) | |
| External Size (W*D*H) | 1500*850*2350mm |
| Exhaust Air Volume | 1500~2000m³/h |
| Air Velocity | 0.3~0.8m/s |
| Noise | ≤60Db(A) |
| Sash | 5mm thickness tempered glass |
| Worktop | Phenolic resin / Epoxy resin / Ceramic / Trespa / SUS / PP |
| Lighting | Full cover type LED lamp with 220V * 20W * 2 |
| Operation Panel | Switch of Lighting,ON/OFF,Electric socket and Blower |
| Sink | PP sink, Epoxy resin sink |
| Electric Socket | Multi-functional type,220V/10A |
| Working Door Opening | 800mm~1000mm |
| Alt Name | FRP Fume Hood |

## FEATURES

1. Corrosion resistance: FRP has a wide range of corrosion resistance, it is suitable for acid gas, toxic and harmful gases and organic solvent gas and dust production operation post and occasions.
2. Operation table: 12.7mm thick phenolic resin board, acid and alkali resistance, moisture proof, anti shock.
3. Adjust door: two section type safety tempered glass, stepless balanced lifting, pulling up and down to stay in any position.
4. Lighting: fluorescent lamp light source and anti-corrosion, isolation light and gas , table light is more than 400 lumens.
5. Operation panel: lighting switch, fan ON/OFF switch, 220V, 10A multi-function two sockets.
6. Light weight, high strength,FRP can withstand 80 °C temperature for a long time, short-term to 130 °C , FRP oxygen index is more than 30,belong to flame retardant materials.

Biolab Scientific Ltd.
Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com