



BENCHTOP AUTOCLAVE BKK-102

BENCHTOP AUTOCLAVE BKK-102

BENCHTOP STEAM STERILIZER



Sterilizing course: Automatic sterilization controlled by computer, easy to operate.
134°C, suitable for 4-6 minutes flash sterilizing.
Safe protection of water lacking.
With over heat and over pressure protection.
After sterilization it will automatically cut the power and then alarm.
Fully stainless steel structure.

SPECIFICATIONS

Model	BKK-102
Capacity	24L
Sterilization Temperature	134°C
Working Pressure	0.22 Mpa
Features	
Sterilizing chamber volume	24L $\Phi 270 \times 410$ mm
Temperature adjust range	105-134°C
Timer range	0-60min
Heat average	$\pm 1^\circ\text{C}$
Power	1.5KW/AC220V 50HZ
Sterilizing plate(mm)	340x200x30(3piece)
Dimension (mm)	560x350x500
Exterior package dimension (mm)	620x410x570
G.W/N.W	20kg/18kg
Alt Name	Benchtop Steam Sterilizer

APPLICATIONS

The table type sterilizers are safely auto-controlled, which are designed for the dental clinics, hospitals, school lab, scientific research institutions and laboratory. And mostly suitable for sterilizing surgical, dental and eye instruments, glassware medicine, culture medium and biological dressing, food, etc.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com