



PORTABLE AUTOCLAVE BKK-1202

PORTABLE AUTOCLAVE BKK-1202

PORTABLE PRESSURE STEAM STERILIZER



Fully stainless steel structure.
Electric or LPG heated.
Working pressure: 0.14~0.16Mpa.
Working temperature: 126°C.
Double scale indication pressure gauge.
Easy to operate, safe, and reliable.

SPECIFICATIONS

Model	BKK-1202
Capacity	24L
Sterilization Temperature	126°C
Working Pressure	0.14-0.16 Mpa
Features	Electric or LPG heated
Sterilizing volume	24L Φ280x390mm
Max. Safety pressure	0.165Mpa
Power	AC220V 50HZ/2KW
Transport dimension(mm)	410x410x550
G.W/N.W	17kg/15Kg
Alt Name	Portable Pressure Steam Sterilizer

APPLICATIONS

The product utilizes saturated steam to rapidly and efficiently sterilize articles. It can be used in hospitals, public health centers, health stations, clinics in factories and mines, scientific research institutes, etc., to sterilize medical equipment, surgical dressings, glass utensils, solutions, substrata. It can also be used as a cooker in plateau areas and be used to make high quality drinking water in industrial and mining enterprises.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com