



BENCHTOP AUTOCLAVE BKK-202

BENCHTOP AUTOCLAVE BKK-202

BENCHTOP STEAM STERILIZER



Indicator light indicates working state.
For 4~6 minutes rapidly sterilize.
Sterilizing temperature and time can be preset.
Steam-water inner circulation system: no steam discharge and the environment for sterilizing will be clean and dry.
Over temperature & over pressure auto-protection.
Safe protection of water lacking.
Exhaust the cool air automatically.
With three stainless steel sterilizing plates.
The chamber of the sterilizer is made of stainless steel.
Automatically shut off with a beep reminding after sterilization.

SPECIFICATIONS

Model	BKK-202
Capacity	24L
Sterilization Temperature	134°C
Working Pressure	0.22 Mpa
Features	
Sterilizing chamber volume	24L Φ 250x520mm
Temperature adjust range	105-134°C
Timer range	0-60min
Heat average	$\leq \pm 1^\circ\text{C}$
Power	1.5KW/AC220V 50Hz(AC110V 60Hz)
Sterilizing plate	400x200x30(3piece)
Dimension	580x480x384
Exterior package dimension	800x580x500
G.W/N.W	50kg/45Kg
Alt Name	Benchtop Steam Sterilizer

APPLICATIONS

The table type sterilizers are safely auto-controlled, which are designed for the dental clinics, hospitals, school lab, scientific research institutions and laboratory. And mostly suitable for sterilizing surgical, dental and eye instruments, glassware medicine, culture medium and biological dressing, food, etc.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com