BioLAB

PRODUCT CATALOG



TOP-PRESS BKV-305

CE ISO9001 CERTIFIED

www.biolabscientific.com

FLOOR STANDING FREEZE DRYER BKV-305

FLOOR TYPE FREEZE DRYER



1. Control
Microprocessor control & New FD upgraded to 7" LCD touch display which can display drying curve, vacuum, condenser temp., run time, ambient temperature.
Controller built with data recorder and USB interface, data can be exporting to computer for analysis.
Equipped with an advanced control system featuring a modular controller for precise and reliable operation.
2. Condenser
Samples can be pre-freezing in condenser chamber, no need of deep freezer; smoothly chamber without coil pipe.
Material is SS304 stainless steel, SS316 is optional.
-60°C condenser is fit for water-based material.

SPECIFICATIONS

Model	BKV-305
Condenser Temperature	-60°C (-110°C Optional)
Ice Condenser Capacity	22 liters
Dry chamber size (D x H)	Φ300x540
Total shelf area	0.09m²
Shelf size	Φ200mm
Shelf space height	70mm
Shelf number	3pcs
Trays number	3pcs
Vials load capacity (Φ12 mm)	(Φ12 mm) : 990(Φ16 mm) : 555(Φ22 mm) : 270
Sample load capacity	0.9 L
Flask	
Dry rack	Included
Cold trap rack	Included
Shelf heating program	-60°C-110°C (Optional)
Cold trap size	Φ270 x 400 mm
Ice removal capacity	6 kg/24 h
Cooling type	Air-cooled
Defrost type	Electric heating defrost
Ultimate vacuum	1 Pa
Vacuum pump	Included
Pump rate	4 L/s
Installed power	1400 W
Voltage	220 V/50 Hz or 110 V/60 Hz (Optional)
Dimensions of host (L x W x H)	540x610x970 mm
Dimensions of vacuum pump	520x140x250 mm
Total weight	165 kg
Alt Name	Floor Type Freeze Dryer

FEATURES

1. Control

Microprocessor control & New FD upgraded to 7" LCD touch display which can display drying curve, vacuum, condenser temp., run time, ambient temperature.
Controller built with data recorder and USB interface, data can be exporting to computer for analysis.
Equipped with an advanced control system featuring a modular controller for precise and reliable operation.

2. Condenser

Samples can be pre-freezing in condenser chamber, no need of deep freezer; smoothly chamber without coil pipe.
Material is SS304 stainless steel, SS316 is optional.
-60°C condenser is fit for water-based material.
-85°C & -110°C condenser is available for capture low eutectic point material.
Independently temperature sensor for condenser.
Equipped with an electric heating defrost system.

3. Refrigeration

Used slight noise of DANFOSS(SECOP) compressor with CFC-FREE refrigerant (R404a, R134a) ensure long life time and energy saving.
For water-based samples, the -55°C condenser is the perfect choice with effective cost. For samples containing solvents or with low eutectic points, the -85°C dual cascade refrigeration condenser provides maximum performance(optional).
All materials in contact with the product are made of inert materials to meet GLP requirements.
All materials of condenser chamber, table-top, racks, trays and drain value are made of SS304 stainless steel to ensure corrosion-resistant and easy to clean, shelves height adjustable.

4. Module design

Flexible customize to meets wide requirements.
-85°C & -110°C condenser support
Various drying chamber available
Shelf heating & program setting
Vacuum regular valve
Condenser heating defrost function
Wide month jar flask support
Nitrogen valve

5. Spare parts

Famous brand spare parts accessories ensure long running time
Swiss DANFOSS Secop brand compressor
DANFOSS pressure control
Refco pressure gauge
PT-100 temperature sensor
Germany Leybold & Japan Ulvac vacuum pump is optional

Biolab Scientific Ltd.
Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com