



VERTICAL LAMINAR AIRFLOW BLVR-302

VERTICAL LAMINAR AIRFLOW BLVR-302

VERTICAL LAMINAR FLOW CABINET - DOUBLE SIDES TYPE



1. With memory function in case of power-failure.
 2. Double sides work bench, 2~4 operators can work together.
- LED Display, Microprocessor control system.
UV Lamp, Emission of 253.7 nanometers for most efficient decontamination
Double Sides, Double sides work bench, operators can sit face to face.

SPECIFICATIONS

Model	BLVR-302
External Size (W*D*H)	1440*660*1770mm
Internal Size (W*D*H)	1340*560*545mm
Work Surface Height	750mm
Display	LED Display
Airflow Velocity	Average of 0.3~0.5m/s
Material	Main Body: Cold-rolled steel with anti-bacteria powder coating Work Table: 304 stainless steel
Pre-Filter	Polyester fiber, washable
HEPA Filter	99.995% efficiency at 0.3µm
Noise	<65dB
Front Window	Manual, 5mm toughened glass, anti-UV
Max Opening	310mm
UV Lamp	30W*1 Emission of 253.7 nanometers
LED Lamp	16W*1
Consumption	600W
Caster	Universal caster with leveling feet
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz
Standard Accessory	LED lamp, UV lamp*2, Base stand
Optional Accessory	Electric height adjustable base stand
Gross Weight	186kg
Package Size (W*D*H)	1590*890*1340mm
Alt Name	Vertical Laminar Flow Cabinet - Double Sides Type


FEATURES

1. With memory function in case of power-failure.
2. Double sides work bench, 2~4 operators can work together.

LED Display, Microprocessor control system.



UV Lamp, Emission of 253.7 nanometers for most efficient decontamination



Double Sides, Double sides work bench, operators can sit face to face.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com