



MULTI-PARAMETER ANALYZER BMET-602

MULTI-PARAMETER ANALYZER BMET-602

BENCHTOP MULTI-PARAMETER ANALYZER

Multi-parameter Analyzer simultaneously measures Ion, Conductivity, Dissolved Oxygen, Temperature that otherwise requires four different meters. With the appropriate probes installed, it can also simultaneously measure several or one parameters.



SPECIFICATIONS

Model	BMET-602
pH	
- Range	-3.00 to 20.00 pH
- Resolution	1.1, 0.01 pH
- Accuracy	± 0.01 pH
- Calibration Points	Up to 6
- Standard Customization	Yes
- Standard Recognition	NIST, GB and DIN buffers
mV	
pX	
ISE	
- Unit	mol/L, mmol/L, g/L, mg/L, µg/L, ppm
Conductivity	
- Reference Temperature	21, 25 °C
Resistivity	
TDS	
Salinity	
Temperature	
Measurement	
- Reading Mode	AutoRead(Fast, Medium,Slow), Timed, Continuous
- Reading Prompts	Reading, Stable, Locked
- Temp. Compensation	ATC, MTC
Data Management	
- Data Storage	501 results each
- GLP Features	Yes
Inputs	
- pH Electrode	BNC(Q9)
- Temp./DO Probe	5-pin aviation connector
- Temp./EC Probe	6-pin aviation connector
Outputs	
- USB	PC
- USB, RS 232	printer

Display Options	
- Backlight	Yes
- Auto Shut-down	2~60 min, off
- IP Rating	IP55
- Date and Time	
General	
- Power	AC Adapter, 100-240 V AC input, DC9V output
- Dimensions	243x195x68 mm
- Weight	901 g(1.98 lb)
Alt Name	Benchtop Multi-parameter Analyzer



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
 Email: info@biolabscientific.com | Website: www.biolabscientific.com