



MULTI-PARAMETER ANALYZER BMET-606

MULTI-PARAMETER ANALYZER BMET-606

PORTABLE MULTI-PARAMETER ANALYZER

Multi-parameter Analyzer simultaneously measures Ion, Conductivity, Dissolved Oxygen, Temperature that otherwise requires four different meters. With the appropriate probes installed, it can also simultaneously measure several or one parameters.



SPECIFICATIONS

Model	BMET-606
pH	
- Range	-2.00 to 20.00 pH
- Resolution	0.1, 0.01 pH
- Accuracy	± 0.02 pH
- Calibration Points	Up to 5
- Standard Customization	Yes
mV	
pX	
ISE	
- Unit	mol/L, mmol/L, g/L, mg/L, µg/L
Conductivity	
- Reference Temperature	20, 25 °C
- Standard Recognition	84 µS/cm, 1413 µS/cm; 12.88 mS/cm
Resistivity	
TDS	
Salinity	
Dissolved Oxygen Concentration	
- Sensor Type	Polarographic
- Barometric Compensation	Yes
- Manual Salinity Factor Correction	Yes
Saturation	
Temperature	
- Relative Accuracy	± 0.2
Measurement	
- Reading Mode	AutoRead(Fast, Medium, Slow), Timed, Continuous
- Reading Prompts	Reading, Stable, Locked
- Temp. Compensation	ATC, MTC
Data Management	

- Data Storage	500 results each
- GLP Features	Yes
Inputs	
- pH Electrode	BNC(Q9)
- Temp./DO Probe	4-pin aviation connector
- Temp./EC Probe	5-pin aviation connector
Outputs	
- USB	PC,printer
Display Options	
- Backlight	Yes
- Auto Shutdown	300, 600, 1200, 1800, 3600sec, off
- IP Rating	IP65
- Date and Time	Yes
General	
- Power	Rechargeable Lithium batter; AC Adapte,100-240 V AC input, DC5V output
- Dimensions	80x255x35 mm
- Weight	400 g(0.88 lb)
Alt Name	Portable Multi-parameter Analyzer



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
 Email: info@biolabscientific.com | Website: www.biolabscientific.com