



DRYING OVEN BODR-7005

DRYING OVEN BODR-7005

DRYING OVEN



LCD Programmable controller (with timing function)
Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable.
Auto-controller of fan speed to prevent damage to the samples.
Large LCD screen to display more data at same time.
Self-check function makes it easy to identify problems.
There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature.
Programmable controller: 7 periods 63 steps, 0~5999min for each period , fan speed 0 to 100% adjustable.
Independent audible and visible temperature-limiting alarm system ensures experiments run safely.

SPECIFICATIONS

| | |
|------------------------------|--------------------------|
| Model | BODR-7005 |
| Electrical Requirement | 220V 50HZ |
| Controller | Programmable LCD display |
| Power Consumption | 3000W |
| Temperature Range | RT+10~250°C |
| Display Resolution | 0.1°C |
| Temperature Stability | ±1°C |
| Temperature Uniformity | ±2.5% (@100°C) |
| Shelves | 3(PCS) |
| Interior Dimension (WxDxH)mm | 1000x510x800 |
| Exterior Dimension (WxDxH)mm | 1140x850x1080 |
| Chamber Volume | 400L |
| Timing Range | 0~5999min |
| Packing Dimension | 101*126*124 |
| CBM | 1.57 |
| Net Weight | 190.00 |
| Gross weight | 238 |
| Alt Name | Drying Oven |

FEATURES

LCD Programmable controller (with timing function)
Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable.
Auto-controller of fan speed to prevent damage to the samples.
Large LCD screen to display more data at same time.
Self-check function makes it easy to identify problems.
There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature.
Programmable controller: 7 periods 63 steps, 0~5999min for each period , fan speed 0 to 100% adjustable.
Independent audible and visible temperature-limiting alarm system ensures experiments run safely.
RS485 connector can connect computer and printer to record the parameters and the variations of temperature.(Option)



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com