



## DRYING OVEN BODR-7102

# DRYING OVEN BODR-7102

## HIGH TEMPERATURE DRYING OVEN



- 304 stainless steel, mirror polishing processing, semicircular arcs at corners easy to clean and maintain. The space between the shelves in the chamber is adjustable.
- PID controller with over temperature alarm and timing function ensures precise and reliable control.
- Ceramic fiber door seal, which can run at high temperature for a long time and has a long service life.
- Programmable controller: 7 periods 63 steps, 0 ~5999mins for each period, can preset boot and shutdown time, adjustable circulating fan.
- Independent over-temperature alarm system ensures experiments running safely.

## SPECIFICATIONS

Model	BODR-7102
Electrical Requirements	AC380V 50HZ
Temperature Range	RT+20°C~400°C
Display Resolution	0.1°C
Temperature Stability	±0.5°C
Ambient Temperature	+5~40°C
Power Consumption	4050W / 4900W
Chamber Volume	100L
Internal Dimension (WxDxH)mm	450x450x450
External Dimension (WxDxH)mm	990x790x990
Shelves	2(pcs)
Timing Range	0~5999min
Packing Dimension	110*92*121
CBM	1.22
Net Weight	180.00
Gross weight	247
Alt Name	High Temperature Drying Oven

## APPLICATIONS

LCD Programmable controller (with timing function)

Provided for desiccation, torrefaction, wax-melting and sterilization in mining enterprises, laboratories and scientific research institutes.



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)