



VACUUM OVEN BOVA-7306

VACUUM OVEN BOVA-7306

VACUUM OVEN

Microprocessor controller (with timing function)

Vacuum oven is designed especially for drying of material which is thermo-sensitive or decomposes and oxidative easily. It can be filled with inert gases, which is especially for a rapid drying of some compound material.



- Microprocessor controller.
- Dual layer tempered glass door for clear observation.
- Minimum heating time 50% less than traditional vacuum oven.
- Interior chamber made from stainless steel with a mirror polished finish making for easy cleaning.
- Standard with vacuum pump.

SPECIFICATIONS

Model	BOVA-7306
Electrical Requirement	AC220V 50HZ
Controller	LED display
Power Consumption	2400W
Temperature Range	RT+10 ~ 200°C
Display Resolution	0.1
Temperature Stability	±1°C
Vacuum Degree	133Pa
Ambient Temperature	+5~40°C
Chamber Volume	90L
Interior Dimension (WxDxH) mm	450x450x450
Exterior Dimension (WxDxH) mm	610x590x1350
Shelves	2pcs (Independent temp. control) 4pcs
Chamber Material	304 Stainless steel
Packing Dimension	75*71*154
CBM	0.82
Net Weight	135.00
Gross weight	169
Alt Name	Vacuum Oven





Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com