



VACUUM OVEN BOVA-7404

VACUUM OVEN BOVA-7404

VACUUM OVEN

Programmability controller (with timing function)

Vacuum oven is designed especially for drying of material which is thermo-sensitive or decomposes and oxidative easily. It can be filled with inert gases, which is especially for a rapid drying of some compound material.



- Microprocessor controller.
- Dual layer tempered glass door for clear observation.
- Minimum heating time 50% less than traditional vacuum oven.
- Interior chamber made from stainless steel with a mirror polished finish making for easy cleaning.
- Standard with vacuum pump.
- Provides programmability for 7 periods and 9 steps for each period making for a total of 63 programmable step.

SPECIFICATIONS

Model	BOVA-7404
Electrical Requirement	AC220V 50HZ
Controller	LCD Programmability controller
Power Consumption	2050W
Temperature Range	RT+10 ~ 200°C
Display Resolution	0.1
Temperature Stability	±1°C
Vacuum Degree	133Pa
Ambient Temperature	+5~40°C
Chamber Volume	125L
Interior Dimension (WxDxH) mm	500x500x500
Exterior Dimension (WxDxH) mm	660x640x1400
Shelves	3pcs
Chamber Material	304 Stainless steel
Packing Dimension	90*85*176
CBM	1.35
Net Weight	275.00
Gross weight	317
Alt Name	Vacuum Oven





Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com