



MULTI CHANNEL PIPETTE BPIP-318

MULTI CHANNEL PIPETTE BPIP-318

MULTICHANNEL VARIABLE VOLUME MICROPIPETTES

Easy Handling

A particular advantage of the new multichannel pipette is the easy operation, e.g., when performing serial pipetting of immunological assays, while making serial dilutions or when filling 96-well plates for cell cultures.

Using innovative material will be lighter.

Pipetting is easy and convenient.

reduce the risk for hands injury when repetitive pipetting.

It can be operated comfortably whether with large hands or small hands.

The ergonomically finger rest takes the load off the hand, no need to grip the pipette tightly, so the pipetting operations can be completed with the fatigue.

True one-hand operated.

The one hand can change the volume and fix the volume easily and conveniently.

The large pipetting button will save pipetting strength. Piston corrosion proof

Light weight-Accurate-Low force

The piston-operated micropipettes provide maximum versatility and optimum quality over the entire volume range.

There are 5 different volume 8 and 12 channels micropipette which cover 0.5 -- 300 µl.



CE-compliant

Volume-change protection

Corrosion-resistant piston and ejector

Completely autoclavable at 121°C (20min)

Color-coded for easy selection of the right tip

4-Position volume display, always clearly visible externally

True one-handed operation for both right-and left-handers.

Rotating dispensing head for optimal pipetting convenience.

Large central pipetting button and separate ejection function.

Short stroke of only 12.5mm to reduce the risk of RSI (Repetitive Strain Injury)

Due to the optimized standard design for the tip cone, it can be compatible with a wide range of tips.

SPECIFICATIONS

Model	BPIP-318
Volume (µl)	10-100
Increment set (µl)	100/50/10
A* ≤ ± (%)	0.8/0.6/4
CV* ≤ (%)	0.3/0.6/2
Increment (µl)	0.1
Type of tips (µl)	200/300
MOQ-5PCS	
Alt Name	Variable Volume 12 channel Micropipette (Ejector 121°C autoclavable)

FEATURES

CE-compliant

Volume-change protection

Corrosion-resistant piston and ejector

Completely autoclavable at 121°C (20min)

Color-coded for easy selection of the right tip

4-Position volume display, always clearly visible externally

True one-handed operation for both right-and left-handers.

Rotating dispensing head for optimal pipetting convenience.

Large central pipetting button and separate ejection function.

Short stroke of only 12.5mm to reduce the risk of RSI (Repetitive Strain Injury)

Diagram illustrating the components and functions of a hair clipper:

- Paraflexion bar:** Moves up and down, high, allowing the clipper to cut hair at different angles.
- Volume adjustment:** Allows the user to adjust the volume of the sound produced by the clipper.
- Volume change control:** Controls the volume of the sound produced by the clipper.
- Paraflexion volume display:** Shows the volume of the sound produced by the clipper.
- Long Paraflexion bar:** Allows the user to cut hair at different angles.
- Engine noise:** The sound produced by the clipper's motor.
- Completely waterproof:** The clipper is designed to be used in wet environments.
- Headset:** The part of the clipper that holds the blades.
- The sound:** The sound produced by the clipper's motor.



Easy calibration institutions



Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com