



MULTI CHANNEL PIPETTE BPIP-322

MULTI CHANNEL PIPETTE BPIP-322

MULTICHANNEL VARIABLE VOLUME MICROPIPETTES

A particular advantage of the new multichannel pipette is the easy operation, e.g., when performing serial pipetting of immunological assays, while making serial dilutions or when filling 96-well plates for cell cultures.

Using the innovative material will be lighter.

Pipetting is easy and convenient.

Reduce the risk for hands injury when repetitive pipetting.

It can be operated comfortably whether with large hands or small hands.

The ergonomically finger rest takes the load off the hand, no need to grip the pipette tightly, so the pipetting operations can be completed with less fatigue.

True one-hand operated.

The one hand can change the volume and fix the volume easily and conveniently.

The large pipetting button will save pipetting strength.

Piston corrosion proof

Light weight - Accurate - Low force

The piston-operated micropipettes provide maximum versatility and optimum quality over the entire volume range.

There are 5 different volume 8 and 12 channels micropipette which the volume cover 0.5-300 µl



CE-compliant

Volume-change protection

Corrosion-resistant piston and ejector

Completely autoclavable at 121°C (20 min)

Color-coded for easy selection of the right tip

4-Position volume display, always clearly visible externally

Large central pipetting button and separate ejection function

True one-handed operation for both right- and left-handers

Rotating dispensing head for optimal pipetting convenience

Due to the optimized standard design for the tip cone, it can be compatible with a wide range of tips.

The Futrmex multichannel Micropipette has the light weight, operated with pipett

SPECIFICATIONS

Model	BPIP-322
Volume (µl)	5-50
Increment set (µl)	50/25/5
A* ≤ ± (%)	0.8/1.4/6
CV* ≤ (%)	0.4/0.8/3
Increment (µl)	0.05
Type of tips (µl)	200
MOQ-5PCS	
Alt Name	Variable Volume 8 channel Micropipette (121°C autoclavable)

FEATURES

CE-compliant

Volume-change protection

Corrosion-resistant piston and ejector

Completely autoclavable at 121°C (20 min)

Color-coded for easy selection of the right tip

4-Position volume display, always clearly visible externally

Large central pipetting button and separate ejection function

True one-handed operation for both right- and left-handers

Rotating dispensing head for optimal pipetting convenience

Due to the optimized standard design for the tip cone, it can be compatible with a wide range of tips.

The Futrmex multichannel Micropipette has the light weight, operated with pipetting strength easily and conveniently.
Short stroke of only 12.5 mm to reduce the risk of RSI (Repetitive Strain Injury)
Individual shafts with seals can be easily unscrewed for cleaning or replacing - eliminates expense and long outages.
Unique tip loading mechanism for perfect tip sealing and light tip ejection, Perfecttip sealing in multichannel micropipette.
Allows tips to be loaded with constant force
Enables even and safe tip sealing to the tip cones with minimum force
Makes tip ejection light and easy



One-handed operation



Easy calibration institutions



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com