



SINGLE CHANNEL PIPETTE BPIP-513

SINGLE CHANNEL PIPETTE BPIP-513

VARIABLE VOLUME SINGLE CHANNEL MICROPIPETTE

Single Channel Pipette is the new standard for microliter measurements. It is top of the line micropipette that is ergonomically designed and easily adjustable. They are commonly used in laboratory, research, chemistry, biology, forensic, pharmaceutical, and drug discovery labs to transfer small quantities of liquid.



Large central pipetting button and separate ejection function
True one-handed operation for both right and left-handers
Completely autoclavable at 121°C(20min)
Volume-change protection
4-Position volume display, always clearly visible externally
Short stroke of only 12.5mm to reduce the risk of RSI (Repetitive Strain Injury)
Corrosion-resistant piston and ejector
Color-coded for easy selection of the right tip

SPECIFICATIONS

Model	BPIP-513
Autoclavable	Ejector 121°C
Volume	0.5-10 µl
Increment (µl)	0.01
Accuracy* $\pm\%$	1
CV* $\leq\%$	0.5
Unit	20
Alt Name	Variable Volume Single Channel Micropipette

APPLICATIONS

Environmental Sciences, Laboratory, Research, Liquid Handling Task, Institutes, Pharmaceutical, Industrial, Microbiology, Chemistry, Biology, Medical, Plasmid Purification.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com