



SINGLE CHANNEL PIPETTE BPIP-519

SINGLE CHANNEL PIPETTE BPIP-519

VARIABLE VOLUME SINGLE CHANNEL MICROPIPETTE

Single Channel Pipette is the new standard for microliter measurements. It is top of the line micropipette that is ergonomically designed and easily adjustable. They are commonly used in laboratory, research, chemistry, biology, forensic, pharmaceutical, and drug discovery labs to transfer small quantities of liquid.



- Large central pipetting button and separate ejection function
- True one-handed operation for both right-and left-handers
- Completely autoclavable at 121°C(20min)
- Volume-change protection
- 4-Position volume display, always clearly visible externally
- Short stroke of only 12.5mm to reduce the risk of RSI (Repetitive Strain Injury)
- Corrosion-resistant piston and ejector
- Color-coded for easy selection of the right tip
- Request Quote

SPECIFICATIONS

Model	BPIP-519
Autoclavable	Ejector 121°C
Volume	500-5000 µl
Increment (µl)	5
Accuracy* $\leq\pm\%$	0.6
CV* $\leq\%$	0.2
Unit	20
Alt Name	Variable Volume Single Channel Micropipette

APPLICATIONS

Environmental Sciences, Laboratory, Research, Liquid Handling Task, Institutes, Pharmaceutical, Industrial, Microbiology, Chemistry, Biology, Medical, Plasmid Purification.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com