



TESTER PETROLEUM EQUIPMENT BPTL-225

TESTER PETROLEUM EQUIPMENT BPTL-225

WATER WASHOUT PROPERTIES TESTER



The instrument shell is made of refined steel plate and coated with glaze, which is durable;

The test bearing chamber and shell fully meet the requirements of the standard method;

Stainless steel water tank with inlet and outlet pipes, aluminum bearing chamber, copper chrome-plated circulating pump, 1/4 HP motor;

Stainless steel heater

The temperature controller of the instrument is an intelligent regulator that integrates temperature control and display and has a microprocessor for PID adjustment;

The design of the motor and belt can start the circulating water pump independently when the test bearing is not started.

SPECIFICATIONS

Model	BPTL-225
Applicable standard	SH/T0109, ASTM D1264
Temperature control accuracy	±0.1°C
Temperature control range	Ambient~100°C
Working temperature	37.8 ± 0.1°C and 79 ± 0.1°C
Rotating speed	600 ± 30 rpm
Flow rate of capillary	5 ± 0.5 ml/s
Power supply	AC220V / 50Hz
Total power	600W
Dimension	500*360*550 mm
Weight	35KG
Alt Name	Water Washout Properties Tester

ITEMS INCLUDED

No	Name	Unit	Quantity
1	Main unit	Set	1
2	Protective shield	Set	1
3	Silicone tube Φ8mm	Meter	1
4	Bearing 6204	PC	2
5	Fuse 20A	PC	4



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com