



TESTER PETROLEUM EQUIPMENT BPTL-257

TESTER PETROLEUM EQUIPMENT BPTL-257

COPPER STRIP CORROSION TESTER

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.



The instrument is suitable to determine the corrosiveness to copper of aviation gasoline, aviation turbine fuels, automotive gasoline, tractor fuels, washing solvent, kerosene distillate, lubricating oil, and other petroleum products. The instrument has functions of temperature controlling, automatic timing and alarming. It adopts LCD temperature controller, heater and electric stirrer to form the constant bath. The temperature controller has timing function. It can control the test time and automatically timing. There will be alarm when finished.

SPECIFICATIONS

Model	BPTL-257
Sample testing positions	Four positions
Sample quantity at one test	4 pieces ~ 12 pieces
Temperature range	Ambient to 100°C, can be set at will
Temperature control accuracy	±1°C
Time controlling range	1 minute ~ 24 hours, can be set at will
Temperature sensor	RTD, Pt100
Ambient temperature	15°C ~ 35°C
Relative humidity	≤ 85%
Total power consumption	≤1800W
Power supply	AC(220±10%)V, 50Hz
Dimension	440x330x560 mm
Net weight	16 kg
Alt Name	Copper Strip Corrosion Tester

APPLICATIONS

Petroleum Industry, PVC Pipe Industry



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com