



## TESTER PETROLEUM EQUIPMENT BPTL-258

# TESTER PETROLEUM EQUIPMENT BPTL-258

## CARBON RESIDUE TESTER

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.



The instrument is suitable to determine the carbon residue of lubricating oils, heavy liquid fuels and other petroleum products. The instrument adopts desktop configuration. The heating furnace and controller are assembled to all-in-one machine. Small dimension and easy to use.

## SPECIFICATIONS

Model	BPTL-258
Test furnace	One furnace with four holes
Heating mode	Electric furnace
Temp. Control range	(0 ~ 520)°C
Temp. Control accuracy	±5°C
Ambient temperature	Room temperature ~ 35°C
Relative humidity	≤ 85%
Total power consumption	1300W
Power supply	AC(220±10%)V, 50Hz
Dimension	350x360x370 mm
Net weight	24 kg
Alt Name	Carbon Residue Tester

## APPLICATIONS

Petroleum Industry, PVC Pipe Industry



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)