



TESTER PETROLEUM EQUIPMENT BPTL-261

TESTER PETROLEUM EQUIPMENT BPTL-261

AUTOMATIC DEMULSIBILITY CHARACTERISTICS TESTER

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.



The instrument is suitable to determine the water separability of petroleum oils and synthetic fluids. It adopts LCD to show the diagram. Intuitive and clear. Man-machine dialog. Menu type input. Easy to use.

SPECIFICATIONS

Model	BPTL-261
Testing hole	4 sample
Stirring rate	(1500±15) r/min
Stirring time	(0~99) min
Timing	(0~99) h
Temperature range	(Room temp.~110)°C
Temperature control accuracy	±0.02°C
Ambient temperature	5°C ~ 40°C
Relative humidity	≤ 85%
Power supply	AC(220±10%)V, 50Hz
Maximum power consumption	1500W
Alt Name	Automatic Demulsibility Characteristics Tester

APPLICATIONS

Petroleum Industry, PVC Pipe Industry



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com