



TESTER PETROLEUM EQUIPMENT BPTL-273

TESTER PETROLEUM EQUIPMENT BPTL-273

ASH CONTENT TESTER

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.



The instrument is composed of a box-type heating furnace, a temperature control stand and an electric heating plate. It is small size and needs less land. The box-type furnace adopts all-in-one structure. Special fire-resistant material and heating components. The heating time is short and it has a long lifetime. Small size and good durability.

SPECIFICATIONS

Model	BPTL-273
Box-type heating furnace	
--Rated temperature	1000°C
--Temperature rising time for empty furnace	≤50 min
--Power consumption for empty furnace	≤800W
--Furnace temperature uniformity	≤15°C
--Heat savings	≤5kW.h
--Thermocouple	WRN-010
--Rated power	2.5 kW
--Power supply	AC220V±10%, 50 Hz
--Size of furnace chamber	200x120x80 mm
--Dimension	575x3850x480
Temperature control stand	
--Maximum control temperature	1200°C
--Temperature controller	DTW2001
--Rated controllable power	5000W
Electric heating plate	
--Heating power	(1~6) grades, continuously adjustable
--Diameter of heating plate	Φ85mm
Alt Name	Ash Content Tester

APPLICATIONS

Petroleum Industry, PVC Pipe Industry



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com