



## BENCHTOP SHAKING INCUBATOR BSBT-102

# BENCHTOP SHAKING INCUBATOR BSBT-102

## SHAKING INCUBATOR



- Large LCD screen to display more data at same time.
- Stainless-steel chamber and platform, easy to clean.
- Big observation windows.
- Microprocessor controller for temperature and shaking speed with timing function.
- Self-check function easy to identify problems.
- Smooth start and stop system prevents liquid spillage.
- Auto-controller of fan speed to prevent damage to the samples.
- Safety door switch, auto pause operation when door is opened.
- R134a refrigerant, imported compressor and fan motor.
- High effective filter provides filtration of bacteria and dust.
- Temperature-limiting alarm system, auto switch off when over-temperature.

## SPECIFICATIONS

Model	BSBT-102
Electrical Requirement	220V 50Hz
Shaking Speed Range	40~300r/min
Amplitude	20mm
Temperature Range	RT+5~65°C
Display Resolution	0.1°C
Power Consumption	650W
Platform Size	350x350
Default Platform	Spring wire racks
Timing Range	0~5999min
Packing Dimension	79*65*65
CBM	0.33
Net Weight	40.00
Gross weight	62
Alt Name	Shaking Incubator

## FEATURES

- Large LCD screen to display more data at same time.
- Stainless-steel chamber and platform, easy to clean.
- Big observation windows.
- Microprocessor controller for temperature and shaking speed with timing function.
- Self-check function easy to identify problems.
- Smooth start and stop system prevents liquid spillage.
- Auto-controller of fan speed to prevent damage to the samples.
- Safety door switch, auto pause operation when door is opened.
- R134a refrigerant, imported compressor and fan motor.
- High effective filter provides filtration of bacteria and dust.
- Temperature-limiting alarm system, auto switch off when over-temperature.
- RS485 connector can connect computer record and inspect the parameters and the variations of temperature. (option)
- Maintenance-free DC Brushless motor, easy to clean.

### Options:

- Programmable Temperature Controller
- Controller board and printer(Nested)
- Independent temperature-limiting alarm

- RS485 connector and software

## APPLICATIONS

Microprocessor controller (with timing function)

Widely applicable for researches on bacteria cultivation, fermentation, hybridization, chemical and biochemical reaction, enzymes and tissues research, which have a high requirement on precision of shaking speed and temperature.

## MORE INFO

Platform used for flask clamp and tube holder. Maximum of flask clamp (Monolayer)



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)