



## BENCHTOP SHAKING INCUBATOR BSCO-203

# BENCHTOP SHAKING INCUBATOR BSCO-203

## BENCHTOP SHAKING INCUBATOR

Equipped with precise cooling system and superior quality, low noise centrifugal fan that provides outstanding temperature uniformity ideal for most low temperature applications. Energy efficient, easy to clean design is an advantage for maximum process stability during microbiological tasks.



The electronic control of closed cycle adjustable heating system  
Stainless steel interior and Electrostatic sprayed exterior  
Call to restore function, without power supply  
With strong influence of intermittent rapid heating system of 200 type and 100B type with air pressure regulating valve  
Flexible and convenient, wide variety of detachable accessories

## SPECIFICATIONS

Model	BSCO-203
Internal dimension/capacity (HxWxD) mm/liter	500 mlx28 (Optionally available 2000 mlx8 or 1000 mlx18 or 500 mlx28 or 250 mlx43)
Voltage(V)	220
Temp. Range °C	4~50
Oscillation frequency Rpm	20~300
Amplitude mm	26
Floating Range °C	±0.1
Alt Name	Benchtop Shaking Incubator

## APPLICATIONS

Cell Culturing, Cell Aeration, Solubility Studies, Sample Preparation, Water Analysis, BOD Measurement, Plating, Breeding Experiments, Research Institutions, Universities, Colleges

## MORE INFO

Microprocessor controller  
Stainless steel interior and Electrostatic sprayed exterior  
LCD display



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada  
Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)