



RECIPROCAL SHAKER BSRP-107

RECIPROCAL SHAKER BSRP-107

SHAKER



Rocking motion angle 9°
10 kg and speed range 10-70 rpm
Double LCDs/LEDs for independent display of time and speed
Continuous or timer operation mode
Electronic time switching clock: 1 min - 99 h 59 min
Wide range of platforms for use with a variety of vessels
Simple appearance, save operating space

SPECIFICATIONS

Model	BSRP-107
Tilt angle	9°
Max. load capacity (with platform)	10kg
Motor type	DC motor
Motor input power	40W
Motor output power	24W
Speed range	10-70rpm
Speed display	LCD
Timer display	LCD
Time settings range	1min~99h59min
Voltage, Frequency	100-240V, 50/60Hz
Power	50W
Weight	9kg
Permissible ambient temperature and humidity	5-40°C, 80%RH
Dimension[WxDxH]	360x410x200mm
Protection class	IP21
Alt Name	Large Multifunctional Transference Rocking Shaker

ACCESSORIES FOR PURCHASE

No	Name	Description
1	Dish platform	SK330.5 Dish platform with non-slip mat and fixed string (8pcs) Dimension [WxD]: 30 x 28.5 cm
2	Silicone mattress	For 16 x 5~15 mL tubes, use with SK330.5
3	Silicone mattress	For 6 x 50 mL tubes, use with SK330.5
4	Universal attachment with 4 bars	SK330.1, Size: 32 x 32 cm Capacity for flask: 25mL x 21 pcs, 50mL x 15 pcs, 100mL x 12 pcs, 250mL x 6 pcs, 500mL x 4 pcs
5	Lengthways roller attachment	SK330.3,, mainly used for separation funnel oscillation extraction applications 500mL x 3 pcs, 250mL x 4 pcs, 100/125mL x 4 pcs, 50mL x 5 pcs
6	Bar	Bar for SK330.1 universal attachment

7	sticks	Connect sticks for double dishes shaker
8	Fixing clip attachment	SK330.2, Size: 32 x 32 cm
9	Fixing clip	For flask volume 25 mL, used with SK330.2 [28 pcs], SK180.2 [9 pcs]
10	Fixing clip	for flask volume 50 mL, used with SK330.2 [16 pcs], SK180.2 [9 pcs]
11	Fixing clip	for flask volume 100 mL, used with SK330.2 [16 pcs], SK180.2 [9 pcs]
12	Fixing clip	for flask volume 200/250 mL, used with SK330.2 [9 pcs], SK180.2 [4 pcs]
13	Fixing clip	for flask volume 500 mL, used with SK330.2 [9 pcs], SK180.2 [2 pcs]



APPLICATIONS

Designed for time-dependent and low rpm sensitive shaking applications such as ELISA washes, enzyme immunoassays, protein synthesis, hybridization, staining/destaining gels, immune precipitation and Western blots, cell culture, pharmaceutical profiling, etc.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com