



STABILITY TEST CHAMBER BTST-1601

STABILITY TEST CHAMBER BTST-1601

LARGE MEDICINE STABILITY TESTING CHAMBER



SPECIFICATIONS

Model	BTST-1601
Temperature control range	0~65°C
Temperature Stability	±0.5°C
Temperature Uniformity	±2°C ~ ±3°C
Humidity Range	35~95%RH
Humidity Stability	±3%RH
Illumination	/
Illumination difference	/
Cooling system/cooling mode	Two sets of Imported compressor work rotationally
Controller	Programmable (touch screen)
Sensor	Temp: Pt100, Humidity: capacitance sensor
Ambient Temperature	RT+5~30°C
Electrical Requirement	AC220V 50Hz
Power Consumption	3750W
Operating Power	1400W
Chamber Volume	500L
Interior Dimension (WxDxH,mm)	670x725x1020
External Dimension (WxDxH,mm)	850x1100x1930
Shelves	4(pcs)
Safety Device	Compressor overheating and overpressure protection, Fan overheating protection, Over temperature protection, Overload protection, Water protections
Remark	1. Build in mini printer 2. Paperless recorder (Option)
Packing Dimension	124*97*213
CBM	2.56
Net Weight	317.00
Gross weight	400
Alt Name	Large Medicine Stability Testing Chamber



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com