



STABILITY TEST CHAMBER BTST-1603

STABILITY TEST CHAMBER BTST-1603

LARGE MEDICINE STABILITY TESTING CHAMBER



SPECIFICATIONS

Model	BTST-1603
Temperature control range	0~65°C
Temperature Stability	±0.5°C
Temperature Uniformity	±2°C ~ ±3°C
Humidity Range	35~95%RH
Humidity Stability	±3%RH
Illumination	/
Illumination difference	/
Cooling systemcooling mode	Two sets of Imported compressor work rotationally
Controller	Programmable (touch screen)
Sensor	Temp: Pt100, Humidity: capacitance sensor
Ambient Temperature	RT+5~30°C
Electrical Requirement	AC380V 50Hz
Power Consumption	3400W
Operating Power	2720W
Chamber Volume	800L
Interior Dimension (WxDxH,mm)	800x590x1650
External Dimension (WxDxH,mm)	1360x890x2000
Shelves	4(pcs)
Safety Device	Compressor overheating and overpressure protection, Fan overheating protection, Over temperature protection, Overload protection, Water protections
Remark	1. Build in mini printer2. Paperless recorder (Option)
Packing Dimension	155*106*224
CBM	3.68
Net Weight	330.00
Gross weight	516
Alt Name	Large Medicine Stability Testing Chamber



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com