



STABILITY TEST CHAMBER BTST-1608

STABILITY TEST CHAMBER BTST-1608

LARGE MEDICINE STABILITY TESTING CHAMBER



SPECIFICATIONS

Model	BTST-1608
Temperature control range	0~65°C
Temperature Stability	±0.5°C
Temperature Uniformity	±2°C ~ ±3°C
Humidity Range	35~95%RH
Humidity Stability	±3%RH
Cooling system/cooling mode	Two sets of Imported compressor work rotationally
Controller	Programmable (touch screen)
Sensor	Temp: Pt100, Humidity: capacitance sensor
Ambient Temperature	RT+5~30°C
Electrical Requirement	AC380V 50Hz
Power Consumption	6000W
Operating Power	4800W
Chamber Volume	1500L
Interior Dimension (WxDxH,mm)	1550x590x1650
External Dimension (WxDxH,mm)	2110x890x2000
Shelves	4(pcs)
Safety Device	Compressor overheating and overpressure protection, Fan overheating protection, Over temperature protection, Overload protection, Water protections
Remark	1. Build in mini printer 2. Paperless recorder (Option) 3. 1000L and 1500L are double doors
Packing Dimension	230*107*224
CBM	5.54
Net Weight	563.00
Gross weight	750
Alt Name	Large Medicine Stability Testing Chamber



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com